



All pavement markings shown are illustrative and shall be installed per NCDOT standards and spaced accordingly.

All crosswalk markings to be replaced in existing locations.

General Notes

1. All parking lines shall be 4" white thermoplastic (typical) in accordance with NCDOT 2018 RSD standard detail 1205.01
2. All lane line shall be 4" white thermoplastic (typical) in accordance with NCDOT 2018 RSD standard detail 1205.01
3. All center lines shall be 4" yellow thermoplastic (typical) in accordance with NCDOT 2018 RSD standard detail 1205.01
4. All bike lane lines/symbols shall be 4" white thermoplastic (typical) in accordance with NCDOT 2018 RSD standard detail 1205.01 & 1205.08
5. All gore areas shall be 4" yellow/white thermoplastic (typical) in accordance with NCDOT 2018 RSD standard detail 1205.09
6. All crosswalks shall be painted in accordance with NCDOT 2018 RSD standard detail 1205.07
7. All traffic symbols shall be painted in accordance with NCDOT 2018 RSD standard details 1205.02 & 1205.08

No.	Revision/Issue	Date

From Name and Address  
**City of Salisbury Engineering**

Project Name and Address  
 Main St. restriping  
 from Kerr Street  
 to Cemetery Street

Project Main St. restriping	Sheet 13
Date 3/26/2021	
Scale NTS	