



NOTES:

1. ALL PAVEMENT CUTS SHALL BE REPAIRED WITHIN A MAXIMUM OF TEN (10) DAYS FROM THE DATE THE CUT IS MADE.
2. CONCRETE TRENCH CAP ON ASPHALT STREETS SHALL BE USED ONLY DURING INCLEMENT WEATHER WHEN ASPHALT PLANTS ARE NOT OPERATING.
3. IN ALL OPEN TRENCHES, BACKFILL SHALL BE COMPACTED TO 95% MAXIMUM DRY DENSITY. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING COMPACTION REQUIREMENTS BY SOILS TESTING CERTIFIED BY A LICENSED PROFESSIONAL GEOTECHNICAL ENGINEER.
4. PUBLIC SERVICE DIRECTOR OR DELEGATE MUST APPROVE OTHER SUITABLE BACKFILL MATERIAL PRIOR TO INSTALLATION.
5. ALL PAVEMENT PATCHES SHALL PROVIDE A UNIFORM AND SMOOTH DRIVING SURFACE.

CITY OF SALISBURY, N.C. STANDARD DETAIL

DATE: JULY 19, 2022

STANDARD TRENCH AND PAVEMENT REPAIR

NOT TO SCALE

STANDARD P-5